

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** EHEIM classicLED plants

**Supplier's address:** Service, Plochingen Straße 54, 73779 Deizisau, DE

**Model identifier:** 4266021 - 1240 mm

**Type of light source:**

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	24 V DC, ausziehbare Haltebügel, Kunststoffadapter für T5/T8		
Mains or non-mains:	NMLS	Connected light source (CLS):	Ei
Colour-tuneable light source:	Ei	Envelope:	-
High luminance light source:	Ei		
Anti-glare shield:	Ei	Dimmable:	Only with specific dimmers

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 550 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	7 700
On-mode power ( $P_{on}$ ), expressed in W	17,3	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	90

			values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	6	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	1 240		
	Depth	33		
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,304 0,287
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value		94	Survival factor	1,00
the lumen maintenance factor		0,96		

(a) : not applicable;

(b) : not applicable;

